



179.00 EUR

incl. 19% VAT, plus [shipping](#)

Support:  [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
- Support INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
- Build-in INTEL®GMA 950 Graphics Core
- Integrated LVDS support 18-bit TFT LCD
- Supports 1x Gigabit LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support Watch dog Technology
- Support Power on Board
- Mini-ITX Form Factor(170mm x 170mm)

|                  |                                                                                  |
|------------------|----------------------------------------------------------------------------------|
| CPU              | INTEL®Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)                      |
| Chipset          | INTEL® 945GSE + ICH7M chipset                                                    |
| Memory           | Build-in INTEL® GMA 950 Graphics Core(Share Memory Size: 128/224MB)              |
| Expansion Slots  | Front Side Bus 533MHz                                                            |
| Storage          | 1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 533/400 SDRAM up to 2 GB |
| Audio            | 1 * PCI slot                                                                     |
| Ethernet LAN     | 2 * Serial ATA2 3Gb/s connectors                                                 |
| LVDS             | 1 * Ultra DMA 100 / 66 IDE connector                                             |
| USB              | Realtek ALC662 6-Channel HD Audio CODEC                                          |
| Special Features | Realtek RTL8111DL PCI-E Gigabit Ethernet LAN                                     |
|                  | Onboard 18-bit dual channel LVDS connector                                       |
|                  | Embedded 6 * USB 2.0/1.1                                                         |
|                  | Intel Diamond Ville Platform                                                     |
|                  | Support ACPI S3                                                                  |
|                  | Support CPU Smart FAN                                                            |
|                  | Support DC FAN                                                                   |
|                  | 2 * USB 2.0/1.1 ports                                                            |
|                  | 1 * Keyboard connector                                                           |
|                  | 1 * RJ-45 port                                                                   |
|                  | 3 * Audio I/O ports ( Line-in, MIC and line-out )                                |
|                  | 1 * VGA port                                                                     |
|                  | 1* COM port for RS-232                                                           |
|                  | 1 * HDTV-OUT                                                                     |
|                  | 1 * Coaxial out                                                                  |
|                  | 1 * +12V DC in                                                                   |
| Rear Panel I / O |                                                                                  |

Internal I / O

2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports

NB / Chassis Fan connectors;

1 \* 32-pin LVDS header &amp; 1 \* GPIO header

1 \* COM header ( COM2 for RS-422/485)

1 \* AUDIO header

1 \* JWDB Pin Header &amp; 1 \* Parallel port

BIOS

Award 8MB DIP Flash ROM

Form Factor

Mini ITX Form Factor(170mmx170mm)

**Product Accessories**

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield
- 1x IDE cable
- SATA-Slim ODD Cable+Power